




Gold Edition: Truck Semi Down Draft Paint Booth are designed to ensure clean and filtered air during the painting process. The air enters through the front ceiling where it is cleaner and travels horizontally from the front to the rear of the booth. This envelops the vehicle with clean air, while the exhaust filter system in the back wall captures overspray. Our booths comply with national requirements set by OSHA and NFPA for paint booth construction.

These booths are suitable for trucks of various sizes, from semi trucks to commercial buses. Custom-sized booths are available, accommodating small to large vehicles. Manufactured with 18 gauge galvanized steel on precision CNC equipment, the booths offer optional double wall construction. All components used are ETL or third-party certified. Our booths feature Nut & Bolt type construction, with precision-punched holes for easy assembly in the shop. They incorporate I-beam construction for heavy-duty structural support. ETL certification is included with the purchase, and our booths are proudly made in the USA.



AIR FLOW

Semi-downdraft booths are a hybrid of downdraft and crossdraft booths that use pressurized air to create a diagonal airflow.



CONFORMS TO
NFPA STD 33
CERTIFIED TO
CSASTD C22.1



MADE
IN
U. S. A.

Standard Features:

- Air tight 18 gauge galvanized steel construction
- 15' H x 11' W entrance doors
- Tube axial fan 1-phase or 3-phase available
- Fluorescent light fixtures
- Draft gauge
- 2 Personnel doors with clear tempered glass
- Intake, Exhaust filters & grids
- All hardware, fasteners and sealants
- Accessories: Rubber gaskets, door seats & hardware included
- Duct packages sold separately**

Optional Upgrades:

- Double wall
- Viewing windows
- Air filtration
- Fire suppression
- Height & length extensions
- Powder coating
- Air-make up heated & non heated
- LED Lights



SCAN FOR MORE
INFORMATION

Available sizes

Model	Dimensions	Lights	Fan	Motor
SMDDT30	16'W x 14'H x 30'L	16	(1) 42" Tube axial	5HP Motor 1PH or 3PH-208-230, 460
SMDDT45	16'W x 16'H x 45'L	22	(1) 42" Tube axial	5HP Motor 1PH or 3PH-208-230, 460V
SMDDT55	16'W x 16'H x 55'L	28	(1) 42" Tube axial	7.5HP Motor 1PH or 3PH-208-230, 460V
SMDDT60	16'W x 16'H x 60'L	34	(1) 48" Tube axial	15HP Motor 1PH or 3PH-208-230, 460V
SMDDT60H	16'W x 16'H x 60'L	34	(1) 48" Tube axial	15HP Motor 1PH or 3PH, (1) 10 Blower intake 2.5MBTU heater